



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model Number: SUPDMB20K

Detachable redundant PDU option for compatible SmartOnline UPS Systems - Hardwired input / L6-30R and C19 output connections



Highlights

- Converts compatible SmartOnline 8 and 10kVA high-voltage UPS configurations for N+1 redundancy or increased capacity when used along with a 2nd compatible UPS power module
- Manual bypass feature enables hot-swappable replacement of both power modules while connected equipment runs uninterrupted
- Hardwired input / L6-30R and C19 output connections

Description

SUPDMB20K combines the output of two compatible SU8000RT3UPM or SU10000RT3UPM UPS power modules for fault-tolerant N+1 or increased capacity configurations. Manual bypass feature enables hot-swappable replacement of both power modules with no disruption in power to connected equipment. (IMPORTANT > compatible only with SU8000RT3UPM and SU10000RT3UPM power modules built after 6/2010 with built-in USB and PARALLEL back panel data connections).

Applications

- Ideal for use as a replacement redundant bypass PDU or means of enabling N+1 or increased capacity for configurations involving two compatible UPS power modules

System Requirements

- For use only with configurations involving two compatible SU8000RT3UPM or SU10000RT3UPM power modules (requires two of the same model power module built after 6/2010 originally shipping with built-in USB and PARALLEL back panel data connections)

Package Includes

- SUPDMB20K parallel PDU
- Parallel cable
- Owner's Manual

Features

Specifications

OVERVIEW	
Model Type	PDU Modules; Outlet Kits

OUTPUT	
Frequency compatibility	50 / 60 Hz
Output nominal voltage	200-240VAC
Overload protection	2 double pole 30A breakers, 8 double pole 20A breakers
Outlet quantity / type	2 L6-30R, 8 C19
INPUT	
Nominal Input Voltage(s) Supported	200V AC; 208V AC; 230V AC; 240V AC; 220V AC
Input connection type	Hardwire
Voltage compatibility (VAC)	200; 208; 230; 240; 220
PHYSICAL	
Shipping Dimensions (HWD/in)	10 x 23.9 x 12.1
Shipping Dimensions (HWD/cm)	25.4 x 60.7 x 30.7
Shipping weight (lbs)	14.52
Shipping weight (kg)	6.6
Unit Dimensions (HWD/in)	20.5 x 7 x 4.5
Unit Dimensions (HWD/cm)	52.1 x 17.8 x 11.4
Unit weight (lbs)	14.52
Unit weight (kg)	6.6
Material of construction	Sheet metal
CERTIFICATIONS	
Certifications	Tested to UL1778 4th Edition (USA), CSA (Canada), EN62040-1
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at <http://www.tripplite.com/sku/SUPDMB20K>.

Copyright © 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.